

Dulux AcraTex VENETIAN PLASTER CERA BRILLANTE WAX

AU\_DA02401

Part A	N4100094-Unit
--------	---------------

**Product Overview**

Venetian Plaster Cera Brillante Wax is a water based high gloss protective wax treatment for interior surfaces that have been coated with Venetian Plaster


**Features And Benefits**

- Ready to use
  - Protects and beautifies
- Easy to apply

**Uses And Typical Specifications**

<b>Uses</b>	VENETIAN PLASTER Cera Brillante Wax is particularly suited to preservative / protection interior Venetian Plaster finishes used in the restoration of old historical buildings such as churches, palaces or villas, interior only; to create surfaces of elevated aesthetic value in all settings whether modern or classic: halls, stairways, bathrooms, living rooms; to add a high gloss elegance to the most refined public places such as hotels, restaurants, shops, etc.																																								
<b>Typical Systems</b>	<p><b>Typical System</b> Interior Gyprock  <b>Preparation Guide</b> Refer Full Du-Spec specification Sheet</p> <table border="1"> <thead> <tr> <th>Coat</th> <th>Product</th> <th>Spread Rate (m<sup>2</sup>/L)</th> <th>WFT (micron)</th> <th>DFT (micron)</th> </tr> </thead> <tbody> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER QUARTZ PRIMER</td> <td>8</td> <td>125</td> <td>54</td> </tr> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER POLISHED STUCCO</td> <td>3.69</td> <td>270</td> <td>168</td> </tr> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER POLISHED STUCCO</td> <td>4.13</td> <td>242</td> <td>150</td> </tr> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER POLISHED STUCCO</td> <td>4.73</td> <td>211</td> <td>131</td> </tr> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER CERA BRILLANTE WAX</td> <td>20</td> <td>50</td> <td>46.75</td> </tr> <tr> <td colspan="4"></td> <td><b>Minimum System DFT</b></td> <td>550</td> </tr> </tbody> </table> <p><b>Notes</b> Typical interior Venetian Plaster</p>					Coat	Product	Spread Rate (m <sup>2</sup> /L)	WFT (micron)	DFT (micron)	1st Coat	VENETIAN PLASTER QUARTZ PRIMER	8	125	54	1st Coat	VENETIAN PLASTER POLISHED STUCCO	3.69	270	168	1st Coat	VENETIAN PLASTER POLISHED STUCCO	4.13	242	150	1st Coat	VENETIAN PLASTER POLISHED STUCCO	4.73	211	131	1st Coat	VENETIAN PLASTER CERA BRILLANTE WAX	20	50	46.75					<b>Minimum System DFT</b>	550
Coat	Product	Spread Rate (m <sup>2</sup> /L)	WFT (micron)	DFT (micron)																																					
1st Coat	VENETIAN PLASTER QUARTZ PRIMER	8	125	54																																					
1st Coat	VENETIAN PLASTER POLISHED STUCCO	3.69	270	168																																					
1st Coat	VENETIAN PLASTER POLISHED STUCCO	4.13	242	150																																					
1st Coat	VENETIAN PLASTER POLISHED STUCCO	4.73	211	131																																					
1st Coat	VENETIAN PLASTER CERA BRILLANTE WAX	20	50	46.75																																					
				<b>Minimum System DFT</b>	550																																				

**Typical Properties**

<b>V.O.C Content</b>	<0.1	<b>Clean Up</b>	Water																									
<b>Meets GBCA VOC Requirement?</b>	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.																											
<b>Application Method</b>	 Pad  <b>Other:</b> Microfibre cloth Tobacco Sponge																											
<b>Application Conditions</b>	<table border="1"> <thead> <tr> <th>Solids By Volume</th> <th colspan="2">93.5</th> <th></th> </tr> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Wet Film Per Coat (microns)</td> <td>62.5</td> <td>100</td> <td>100</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td>66.7</td> <td>93.5</td> <td>93.5</td> </tr> <tr> <td>Recoat Time (min)</td> <td>120</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m<sup>2</sup>/L)</td> <td>15</td> <td>10</td> <td>10</td> </tr> </tbody> </table>				Solids By Volume	93.5				Min	Max	Recommended	Wet Film Per Coat (microns)	62.5	100	100	Dry Film Per Coat (microns)	66.7	93.5	93.5	Recoat Time (min)	120			Theoretical Spread Rate (m <sup>2</sup> /L)	15	10	10
Solids By Volume	93.5																											
	Min	Max	Recommended																									
Wet Film Per Coat (microns)	62.5	100	100																									
Dry Film Per Coat (microns)	66.7	93.5	93.5																									
Recoat Time (min)	120																											
Theoretical Spread Rate (m <sup>2</sup> /L)	15	10	10																									

Health And Safety			
<b>MSDS Number</b>	DLX002906	<b>Using Safety Precautions</b>	Keep out of reach of children. Read the label before opening or using. Avoid breathing vapour. Wear protective clothing, gloves, eye/face protection and suitable respirator/dust mask as required. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use. Wash hands, face and all exposed skin thoroughly after handling. .
<b>MSDS Link</b>	<a href="https://go.lupinsys.com/duluxgroup/harms/public/materials/81ba0467baadbc094caa0e9dfff2a48b-published/individual">https://go.lupinsys.com/duluxgroup/harms/public/materials/81ba0467baadbc094caa0e9dfff2a48b-published/individual</a>		
<b>Health Effects</b>	Causes skin irritation. May cause an allergic skin reaction.	<b>Flammability</b>	Combustible liquid. Keep away from all sources of ignition - No smoking.
<b>Protective Equipment</b>	OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES	<b>Storage</b>	Store in a well-ventilated place and away from oxidising agents and foodstuffs
<b>Disposal</b>	Avoid release to the environment.		
<b>In the case of emergency, please call 1800 033 111</b>			

Transport And Storage			
<b>Pack A</b>	N4100094-Unit	<b>Flash Point</b>	>60 Deg C

**Disclaimer**

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.  
DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "AcraTex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427