


Dulux AcraTex VENETIAN PLASTER OMBRA

AU_DA02687

Part A	N4100088/9-Unit	Image	
--------	-----------------	-------	--

Product Overview


Venetian Plaster Ombra is a water based tint able / clear finish for interior surfaces that have been coated with Venetian Plaster

Features And Benefits

- | | |
|---|---------------|
| <ul style="list-style-type: none"> • Ready to use • Protects and beautifies | Easy to apply |
|---|---------------|

Uses And Typical Specifications

Uses	VENETIAN PLASTER Ombra Gloss Glaze is particularly suited to preservative / protection and highlight interior Venetian Plaster finishes used in the restoration of old historical buildings such as churches, palaces or villas, interior only; to create surfaces of elevated aesthetic value in all settings whether modern or classic: halls, stairways, bathrooms, living rooms; to add gloss elegance to the most refined public places such as hotels, restaurants, shops, etc.																																		
Typical Systems	<p>Typical System Interior Gyprock</p> <p>Preparation Guide Refer Full Du-Spec specification Sheet</p> <table border="1" data-bbox="399 1422 1436 1601"> <thead> <tr> <th>Coat</th> <th>Product</th> <th>Spread Rate (m²/L)</th> <th>WFT (micron)</th> <th>DFT (micron)</th> </tr> </thead> <tbody> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER QUARTZ PRIMER</td> <td>8</td> <td>125</td> <td>54</td> </tr> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER MODELLO</td> <td>2.045</td> <td>490</td> <td>350</td> </tr> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER BAUTA</td> <td>11.2</td> <td>91</td> <td>15</td> </tr> <tr> <td>1st Coat</td> <td>VENETIAN PLASTER OMBRA</td> <td>11.2</td> <td>91</td> <td>15</td> </tr> <tr> <td colspan="4" style="text-align: right;">Minimum System DFT</td> <td>434</td> </tr> </tbody> </table> <p>Notes Typical interior Venetian Plaster Bauta Metallic plus tinted VP Ombra tinted Glaze</p>					Coat	Product	Spread Rate (m ² /L)	WFT (micron)	DFT (micron)	1st Coat	VENETIAN PLASTER QUARTZ PRIMER	8	125	54	1st Coat	VENETIAN PLASTER MODELLO	2.045	490	350	1st Coat	VENETIAN PLASTER BAUTA	11.2	91	15	1st Coat	VENETIAN PLASTER OMBRA	11.2	91	15	Minimum System DFT				434
Coat	Product	Spread Rate (m ² /L)	WFT (micron)	DFT (micron)																															
1st Coat	VENETIAN PLASTER QUARTZ PRIMER	8	125	54																															
1st Coat	VENETIAN PLASTER MODELLO	2.045	490	350																															
1st Coat	VENETIAN PLASTER BAUTA	11.2	91	15																															
1st Coat	VENETIAN PLASTER OMBRA	11.2	91	15																															
Minimum System DFT				434																															

Typical Properties																															
V.O.C Content	<1	Clean Up	Water																												
Sizes	1.25L																														
Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.																														
Application Method	 Pad Other: Microfibre or Soft Cotton cloth Soft Sponge																														
Application Conditions	<table border="1"> <thead> <tr> <th colspan="4">Solids By Volume</th> </tr> <tr> <th></th> <th>93.5</th> <th></th> <th></th> </tr> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Wet Film Per Coat (microns)</td> <td>62.5</td> <td>100</td> <td>100</td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td>66.7</td> <td>93.5</td> <td>93.5</td> </tr> <tr> <td>Recoat Time (min)</td> <td>120</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td>11</td> <td>11</td> <td>11</td> </tr> </tbody> </table>			Solids By Volume					93.5				Min	Max	Recommended	Wet Film Per Coat (microns)	62.5	100	100	Dry Film Per Coat (microns)	66.7	93.5	93.5	Recoat Time (min)	120			Theoretical Spread Rate (m ² /L)	11	11	11
Solids By Volume																															
	93.5																														
	Min	Max	Recommended																												
Wet Film Per Coat (microns)	62.5	100	100																												
Dry Film Per Coat (microns)	66.7	93.5	93.5																												
Recoat Time (min)	120																														
Theoretical Spread Rate (m ² /L)	11	11	11																												

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Apply to freshly applied but dry Venetian Plaster.
Application Procedure And Equipment	<ul style="list-style-type: none"> Apply Bauta with a soft Sponge in a circular movement, or in short strokes depending on the desired finish. Avoid excess material on the sponge to prevent dripping. Many be applied in multiply coats using different metallic 's can also be tinted or blended with Ombra clear finish to product high impact finishes.

Health And Safety			
Using Safety Precautions	Keep out of reach of children. Read the label before opening or using. Avoid breathing vapour. Wear protective clothing, gloves, eye/face protection and suitable respirator/dust mask as required. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use. Wash hands, face and all exposed skin thoroughly after handling. .	Health Effects	Causes skin irritation. May cause an allergic skin reaction.
Protective Equipment	OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES	Storage	Store in a well-ventilated place and away from oxidising agents and foodstuffs
Disposal	Avoid release to the environment.		
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Size	Weight
1.25L	Silver 1.625 kg Gold 1.550 kg Bronze 1.600 kg Copper 1.263 kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "AcraTex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427